

<b>MODEL C</b>	
<b>ENGINE SPECIFICATIONS</b>	
<b>Manufacturer/Model</b>	Kohler CH20 2 cyl
<b>Displacement</b>	624CC (38.0 cu. in.)
<b>HP/RPM</b>	20 @ 3600
<b>Max Torque (ft-lbs)</b>	32 @ 2500
<b>Fuel</b>	Gasoline (unleaded)
<b>Fuel Capacity</b>	3.0 (11.4 litre)
<b>Cooling System</b>	Air
<b>Lubrication System</b>	Full Pressure w/Filter
<b>Muffler</b>	Engine Tuned (Lo Tone)
<b>ELECTRIC SYSTEM</b>	
<b>Battery</b>	12 Volt (230CCA)
<b>Charging System</b>	15 Amp Alternator
<b>Ignition</b>	Electronic Capacitive Discharge
<b>Starter</b>	12 Volt Electric, Key and Solenoid Operated
<b>Interlock Switch System</b>	Ignition Lockout By Seat Switch, Transmission Neutral And Blade Clutch
<b>TRACTOR DRIVE</b>	
<b>Transmission</b>	Dual Hydrostatic Eaton Model 7, Each Wheel Independently Driven
<b>Steering</b>	Hand Lever Control, Individual Drive Wheel
<b>Forward Speed Control</b>	Precision Friction Lock lever, Cruise Control, With Neutral-Park Position
<b>Brake</b>	Dynamic Braking Through Hydrostatic Transmission
<b>Parking Brake</b>	Standard
<b>Final Drive</b>	Gear Drive Axle
<b>Ground Speed (KM/H)</b>	0-8 infinitely Variable (Forward Or Reverse)
<b>Turning Radius</b>	Zero (0")
<b>MOWER DECK</b>	
<b>Cutting Width (In)</b>	36 to 56 (8 Decks)
<b>Cutting Height (In)</b>	1 to 4 (2.54 to 10.6 cm)
<b>Blade</b>	0.164 Inch Stamped Steel, 1566 HR Alloy, Tempered
<b>Max Blade Speed</b>	2900 RPM (16700 FPM With 22" Blade)
<b>Blade Drive</b>	Splined PTO Drive Shaft/2 High Speed U-Joints, Shear pin for shock protection on timed gear drive on deck (DSD62 has 3 Belt Driven Spindles)
<b>Blade Clutch &amp; Brake</b>	Manual Belt Tightener/Band Brake
<b>Deck Suspension</b>	Torsion-Flex Frame With Caster Wheels and Counterweight Springs
<b>CONSTRUCTION</b>	
<b>Frame/Body</b>	Frame All Welded Unitized Steel Frame/14 Ga Steel Body Shell
<b>Mower Deck</b>	11 Ga Welded Steel
<b>GHS Catcher &amp; Chutes</b>	Moulded Cross-Linked Polyethylene (High Impact Material, UV Stabilized)
<b>Seat</b>	Contour-Moulded With Nylon Backed Vinyl Cover And Integral Foam Cushion
<b>GHS (OPTIONAL)</b>	
<b>Blower</b>	4.5 x 10.5 x 1/2 Three Blade Steel Paddle Wheel
<b>Max Blower Speed</b>	4000
<b>Grass Catcher Capacity</b>	9.5 Bushel (335 litres) {6.7 Bushel (238 litres) optional}
<b>Full Signal</b>	12 Volt Horn Operated By Oscillating Vane Switch on Grass Delivery Spout
<b>Powerfil</b>	Oscillating Delivery Spout Spreads Material Inside Catcher
<b>TIRE SIZE</b>	
<b>Deck Caster Wheel</b>	Standard 2.80/2.50-4 Pneumatic (4 Ply)
<b>Drive</b>	18 x 8.50-10
<b>Rear Tire</b>	13 x 6.50-6
<b>DIMENSIONS (INCHES)</b>	
<b>Outside Dimensions</b>	49-1/2 H x 43 W x 89L
<b>Wheel Base (Tractor)</b>	42-1/2
<b>Tread Width (Tractor)</b>	29/03/2004
<b>CURB WEIGHT (APPROXIMATE KGS)</b>	
<b>SD Tractor Only</b>	282
<b>GHS Tractor Only</b>	341
<b>Tractor and Mower</b>	432