

GEN-SET



GH 2000



PORTABLE POWER



Technical Data

Model	GH 2000
Type	Portable
Speed	3000 RPM
Phase / Voltage	1 / 240
Frequency	50 Hz
Max power kW	2.2kW
Continuous Output	2.5kVA
Noise Level (dBA @ 7 m)	72
Frame	Small roll frame

Engine

Manufacturer	Honda
Engine Model	GX 160
Type	O.H.V.
Starting	Recoil start
Fuel	Unleaded petrol
Run Time	3.1 hr @ 100% 5hrs @ 60%
Consumption	1.2 L/h
Tank Capacity	3.6 L
Engine Protection	Low oil level
HP 3600 rpm max	5.5
Cubic Capacity	163 Cm ³
Oil Capacity	0.6 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic distortion	Less than 5%
protection class	IP 23
insulation class	Class H

Outlets

Outlet	2 x 10amp switched with thermal overload
--------	--

Dimensions and Weight

Length	65 Cm
Width	42 Cm
Height	45 Cm
Weight	32 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long range Tank	15 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only