GEN-SET

GH 2700

PORTABLE POWER

Technical Data	
Model	GH 2700
Type	Portable
Speed	3000 RPM
Frequency	50 Hz
Phases / Voltage	1 / 240
Max power kW	2.7kW
Max Output kVA	3.3kVA
Noise Level (dBA @ 7 m)	72
Frame	Small Roll Frame
Engine	
Manufacturer	Honda
Engine Model	GX 200
Type	O.H.V.
Starting	Recoil start
Fuel	Unleaded petrol
Run Time	2.7 hrs @ 100% , 4hrs @ 60%
Consumption	1.3 L/h
Tank Capacity	3.6 L
Engine Protection	Low oil level
HP 3600 rpm max	6.5
Cubic Capacity	196 Cm3
Oil Capacity	0.6 L
Alternator	
Alternator Brand	Meccalte
Type	Brushless
Harmonic distortion	Less than 5%
protection class	IP 23
insulation class	Class H
Outlets	
Outlet	2 x 10amp switched with thermal overload
Dimensions and Weight	
Length	65 Cm
Width	42 Cm
Height	45 Cm
Weight	39 Kg
Options	
Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long range Tank	15 Litre Capacity

.

The information given in this brochure is the assistance of users and is intended for guidence only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illistration purposes only