

GEN-SET



# GH 5000E



PORTABLE POWER



**POWERED by**  
**HONDA™**

## Technical Data

|                         |                           |
|-------------------------|---------------------------|
| Model                   | GH 5000E                  |
| Type                    | Portable                  |
| Speed                   | 3000 RPM                  |
| Frequency               | 50 Hz                     |
| Phases / Voltage        | 1 / 240                   |
| Max power kW            | 5 kW                      |
| Max Output kVA          | 5.5 kVA                   |
| Noise Level (dBA @ 7 m) | 76                        |
| Frame                   | Large roll Frame          |
| Electric Start          | Battery carrier and leads |

## Engine

|                   |                          |
|-------------------|--------------------------|
| Manufacturer      | Honda                    |
| Engine Model      | GX 340                   |
| Type              | O.H.V.                   |
| Starting          | Hand start @ Electric    |
| Fuel              | Unleaded petrol          |
| Run Time          | 3 hr @ 100%, 4.2hrs @60% |
| Consumption       | 2.1 L/h                  |
| Tank Capacity     | 6.5 L                    |
| Engine Protection | Low oil level            |
| HP 3600 rpm max   | 11                       |
| Cubic Capacity    | 337 Cm3                  |
| Oil Capacity      | 1.1 L                    |

## Alternator

|                     |              |
|---------------------|--------------|
| Alternator Brand    | Meccalte     |
| Type                | Brushless    |
| Harmonic distortion | Less than 5% |
| protection class    | IP 23        |
| insulation class    | Class H      |

## Outlets

|        |  |
|--------|--|
| Outlet | 10amp + 15amp switched with thermal overload |
|--------|--|

## Dimensions and Weight

|        |       |
|--------|-------|
| Length | 85 Cm |
| Width  | 57 Cm |
| Height | 60 Cm |
| Weight | 57 Kg |

## Options

|                 |  |
|-----------------|--|
| Outlets         | Weather protected IP33 & Weatherproof IP66 |
| Protection      | RCD/ELCB IP30 or IP66                      |
| Long range Tank | 15 Litre Capacity                          |
| Wheel kits      | Two wheel or four wheel                    |
| Frames          | Extra large Roll Frames                    |
| Battery         | Wet Charged                                |
| Fuel            | LPG Conversion                             |
| Control Systems | Auto start, 2 Wire remote, AMF, SMS        |
| Alternators     | Oversized, Single or Three Phase           |

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only