

HONDA

Model	G200
Type	4-stroke, side valve, single-cylinder, horizontal shaft
Bore & Stroke	67 x 56 mm (2.6 x 2.2 in)
Displacement	197 cm ³ (12.0 cu in)
Compression Ratio	6.5:1
Net Power	3.4kW (4.5HP) at 3,600 rpm
Continuous Rated Power	2.7kW (3.6HP) at 3600 rpm
Maximum Net Torque	8.2 Nm (6.8 lbf ft) at 2,500 rpm
Ignition System	Flywheel magneto
Starting System	Recoil starter
Cooling System	Forced-air
PTO Shaft Rotation	Counter-clockwise (from P.T.O. side)
Recommended Fuel	Unleaded
Lubrication System	Splash
Recommended Oil	10W/30 API SG
Oil Capacity (litres)	0.7
Fuel Tank Capacity (litres)	3.5
Dimensions (LxWxH)	400mm x 327mm x 425mm

**The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE J1349 at 3600 rpm (or 7000rpm for mini 4 engines). Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the operating speed of the engine in application, environmental conditions, maintenance and other variables