

HONDA

Model	GX200
Type	4-stroke, overhead valve, single-cylinder, horizontal shaft
Bore & Stroke	68 x 54 mm (2.7 x 2.1 in)
Displacement	196 cm ³ (12.0 cu in)
Compression Ratio	8.5:1
Net Power	4.1kW (5.5HP) at 3,600 rpm
Continuous Rated Power	3.7kW (5.0HP) at 3,600 rpm
Maximum Net Torque	12.4 Nm (9.1 lbs ft) at 2,500 rpm
Ignition System	Transistorised magneto ignition
Starting System	Recoil (Electric Starter Optional)
Cooling System	Forced-air
PTO Shaft Rotation	Counter-clockwise (from P.T.O. side)
Fuel Consumption at Rated Power	1.7 L/h at 3,600 rpm
Recommended Fuel	Unleaded
Lubrication System	Splash
Recommended Oil	10W/30 API SG
Oil Capacity (litres)	0.6
Fuel Tank Capacity (litres)	3.1
Dimensions (LxWxH)	313mm x 376mm x 346mm
Dry weight (kg)	16.0kg
Other Options	2:1 Reduction - 2:1 Reduction with Clutch - 6:1 Reduction

**The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE J1349 at 3600 rpm (or 7000rpm for mini 4 engines). Mass production engines may vary from this value.

Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the operating speed of the engine in application, environmental conditions, maintenance and other variables