

HONDA

Model	GXV670
Engine Type	Air-cooled, 4-Stroke, OHV, 90L V-twin
Bore x Stroke	77 x 66 mm (3.0 x 2.6 in)
Displacement	614 cm ³ (37.5 cu in)
Compression Ratio	8.3 : 1
Net Horse Power Output*	15.5kW (20.8HP) at 3,600 rpm
Net Torque	44.4 Nm (32.7 lbs ft) at 2,500 rpm
Ignition System	Transistorized magneto ignition
Starting System	Electric Starter
PTO Shaft Rotation	Counterclockwise (from PTO shaft side)
Carburetor	Horizontal type, 2 barrel, butterfly valve
Lubrication System	Full Pressure
Governor System	Centrifugal Mechanical
Air Cleaner	Dual Element Type
Oil Capacity	2.5l (2.6 US qt, 2.2 Imp qt) w/filter replacement
Oil Filter	Automotive spin on style
Dimensions (L x W x H)	464mm(18.3 in) x 473mm (18.6 in) x 449mm (17.7 in)
Dry Weight	45 kg (99.0 lbs)

* The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE J1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the operating speed of the engine in application, environmental conditions, maintenance and other variables.